









AQUAPRESS THINWALL is the latest generation dripline with self-compensating flat dripper, equipped with three systems that guarantee functionality and reliability in long-lasting irrigation systems on uneven and sub-irrigated soils.

| TECHNICAL FEATURES | Diameter 16 mm | | |
|-----------------------------|-------------------------------|--------------------------|--------------------------|
| Internal diameter | 16,10 mm | | |
| Thickness | 15 mil 0,38 mm | 18 mil 0,45 mm | 24 mil 0,60 mm |
| Min working pressure | 0,50 bar | | |
| Max working pressure | 1,80 bar | 2,00 bar | 2,50 bar |
| Max washing pressure* | 2,00 bar | 2,20 bar | 2,70 bar |
| Closing pressure | 0,25 bar | | |
| Nominal flow rate (1,0 bar) | 1,00 - 1,60 - 2,40 - 3,80 l/h | | |
| Dripper spacing | 20 ÷ 150 cm | | |
| Reel length ^o | 1200 m | 800 m | 600 m |

| Diameter 22 mm | | | | |
|-------------------------------|--------------------------|--------------------------|--|--|
| 13,80 mm | | | | |
| 15 mil 0,38 mm | 18 mil 0,45 mm | 24 mil 0,60 mm | | |
| 0,50 bar | | | | |
| 1,50 bar | 1,80 bar | 2,20 bar | | |
| 1,70 bar | 2,00 bar | 2,40 bar | | |
| 0,25 bar | | | | |
| 1,00 - 1,60 - 2,40 - 3,80 I/h | | | | |
| 20 ÷ 150 cm | | | | |
| 800 m | 700 m | 500 m | | |

FEATURES AND BENEFITS

- Self-compensating system (PC) ensures a constant flow rate when the operating pressure varies (0.50 ÷ 3.50 bar)
- Anti-siphon system (AS) in sub-irrigation systems, prevents the suction of earth in the dripper when the system is shut down
- No-drain system (ND) prevents the dripline from emptying by closing the dripper below 0.25 bar. It allows impulse irrigation thanks to the simultaneous opening of all the drippers at a pressure of 0.30 bar
- Excellent coefficient of variation (CV)
- Wide range of thicknesses, flow rates, diameters and spacings for every drip irrigation need
- Blue stripe to indicate the correct installation upwards on the ground
- High resistance to UV rays, chemicals and acids used in agriculture
- · Warranty:
- 3 years manufacturing / material defects 5 years - environmental stress cracking



Ideal for horticultural and tree crops. Excellent for subirrigation and impulse irrigation in greenhouses and open fields.



^{*} For a duration of about half an hour with the terminals open