



since 1967

GOLD-DRIP SUPER



GOLD-DRIP SUPER is a dripline with short cylindrical dripper and turbulent flow, self-cleaning with double built-in inlet filter.

SUPER is the most advanced and economical version with 3 dispensing holes, with a compact dripper to ensure minimum pressure drops and excellent irrigation uniformity with considerable wing lengths.

TECHNICAL FEATURES	Diameter 16 mm
Internal diameter	14,20 mm
Thickness	36 mil 0,90 mm
Max working pressure	3,00 bar
Max washing pressure*	3,50 bar
Nominal flow rate (1,0 bar)	2,00 - 4,00 l/h
Dripper spacing	20 ÷ 150 cm
Reel length ^o	400 m

Diameter 16 mm
14,00 mm
40 mil 1,00 mm
3,00 bar
3,50 bar
2,00 - 4,00 l/h
20 ÷ 150 cm
400 m

Diameter 20 mm
17,80 mm
45 mil 1,10 mm
3,00 bar
3,50 bar
2,00 - 4,00 - 8,00 l/h
20 ÷ 150 cm
300 m

FEATURES AND BENEFITS

- Ideal for long-term surface irrigation systems
- Uniformity of emission over the entire length of the wing on flat ground
- · Resistant to mechanized installation
- High resistance to UV rays, chemicals and acids used in agriculture
- Available with constant pitch and alternating pitch distant drop
- Low technological variation coefficient (CV)
- · Possibility of being collected, rewound and reused
- Drip tape compliant with UNI EN ISO 9261 standards and certified by the IIP (Italian Institute of Plastics).



Suitable for vineyards, olive groves, tree crops and orchards, in greenhouses and open fields. Also suitable for hedges, flower beds and ornamental gardens.



^{*} For a duration of about half an hour with the terminals open