



since 1967

GOLD-DRIP



GOLD-DRIP F6 is a dripline with long cylindrical turbulent flow dripper, self-cleaning with double built-in inlet filter.

F6 is the classic version of the dripline with 6 delivery holes for better water distribution on sandy soils.

TECHNICAL FEATURES	Diameter 16 mm
Internal diameter	13,80 mm
Thickness	45 mil 1,10 mm
Max working pressure	3,50 bar
Max washing pressure*	4,00 bar
Nominal flow rate (1,0 bar)	2,00 - 4,00 l/h
Dripper spacing	20 ÷ 150 cm
Reel length ^o	400 m

Diameter 20 mm	
17,80 mm	
45 mil 1,10 mm	
3,00 bar	
3,50 bar	
2,00 - 4,00 l/h	
20 ÷ 150 cm	
300 m	

FEATURES AND BENEFITS

- Ideal for long-term surface irrigation systems
- Uniformity of emission over the entire length of the wing on flat ground
- · Resistant to mechanized installation
- High resistance to UV rays, chemicals and acids used in agriculture
- Available with constant pitch and alternating pitch distant drop
- Low technological variation coefficient (CV)
- · Possibility of being collected, rewound and reused
- Drip tape compliant with UNI EN ISO 9261 standards and certified by the IIP (Italian Institute of Plastics).



Suitable for vineyards, olive groves, tree crops and orchards, in greenhouses and open fields.

^{*} For a duration of about half an hour with the terminals open